



AVC-PRHN21FT


2.1MP IP PINHOLE LENS PIR TYPE CAMERA


OVERVIEW


- H.264 Compression
- 1/2.8" 2 Megapixel CMOS Sensor
- Effective Pixels: 1920 x 1080
- 3.7mm Fixed Lens
- 2MP @ 30fps
- 0.001 Lux @ F1.2, AGC ON, 0 Lux with IR
- DWDR
- 12V DC / PoE

DIMENSIONS

Unit: inch(mm)







OPTIONAL ACCESSORIES



SPECIFICATIONS

CAMERA	
Image Sensor	1/2.8" CMOS Sensor
Image Size	1920x1080
Electronic Shutter	1/25s ~ 1/100000s
Minimum Illumination	Color: 0.001lux@F1.2, AGC ON, B/W: 0lux with IR
IR On/Off Control	No
Focal Length	3.7mm Fixed Lens
Angle of View	No
Angle Adjustment	No
IR Distance	No
Wide Dynamic Range	DWDR
S/N Ratio	N/A
Video Compression	H.264 / MJPEG
Video Resolution	1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Video Frame Rate	60Hz: 1080P (1~30fps) / 720P (1~30fps)
OPERATIONAL	
Video Bitrate	32 Kbps ~ 2048 Kbps
Day / Night	
Video Encode	VBR / CBR
BLC Mode	
HLC	N/A
White Balance	N/A
ROI	3 ROI
Gain Control	N/A
Digital Noise Reduction	3D DNR
Defog	N/A
Quality	Five levels under VBR; Freely adjustable under CBR
Audio Compression	No
Audio In	No
Audio Out	
	Motion Alarm
	No
Alarm Out	No
NETWORK	
Al Perimeter Protection	
	RJ45 x 1
	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Network remote storage
Storage Card	No .
	IE browsing
	Watermark, IP Address Filtering, Access Policy, RTSP Authentication, User Authentication
Network Max. Users	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Mobile	iPhone, Android
Video Output RS485	No No
	INO
GENERAL	DC 12V / PoE
Power Supply Power Consumption	200mA
	-13° ~ 131° F (-25° ~ 55° C), 10% ~ 90% humidity
Operating Temperature Ingress Protection	-13^~131^F (-25^~55^C), 10% ~ 90% numidity
Ingress Protection Dimensions	4.72 x 2.75in (120 x 70mm)
	4.72 x 2.75in (120 x 70mm) 0.26Lbs (120g)
vveignt	0.20L0s (120g)