#### AVC-VNN41FLT/2.8 4MP H.265 NETWORK IR OUTDOOR VANDAL DOME CAMERA





## 4MP H.265 NETWORK IR OUTDOOR VANDAL DOME CAMERA

4MP H.265 NETWORK IR OUTDOOR VANDAL DOME CAMERA WITH ADVANCED VIDEO ANALYTICS

The AVC-VNN41FLT/2.8 is our newest 4MP H.265 Vandal Dome Outdoor IP Camera with a 2.8mm fixed lens and featuring our newest generation of video analytics. This camera supports True Day/Night mode, True WDR capabilities and also includes a microSD memory card slot for standalone recording applications. The AVC-VNN41FLT/2.8 can be powered by both PoE(802.3af) and DC12V and also includes a hardware reset button. Integrated Video Analytics include Missing/Abandoned Objects, Line Crossing, Heat Map, Vehicle/People Counting and Facial Detection.

## **FUNCTIONS**

- 4MP H.265 Real Time Encoding
- Maximum Resolution: 2592 x 1520
- Fixed 2.8mm Lens
- Smart IR Illumination Up to 98ft(30m).
- True Day / Night
- Hardware Reset
- Built-in Micro SD Card Slot
- Supports Three Streams
- NAT/P2P Function Optional
- Video Analytics: Line Crossing, Heat Map, People / Car Counting, Facial Detection, etc.
- Supports Remote Monitoring by Smart Phones & Tablet PCs with iOS and Android OS
- IP67 Outdoor Rating
- IK10 Ingress Protection
- DC12V / PoE (802.3af) <7W
- NDAA Compliant

### **OPTIONAL ACCESSORIES**



AVM-DDMTS-W-TL1




AVM-EWMTS-W-TL1




Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

## DIMENSIONS







# **SPECIFICATIONS**

:

CAMERA	
	1/3" Progressive Scan CMOS
Resolution	
	2592 x 1520
	1/30s to 1/100.000s
Iris Type	Fixed Iris
	Up to 98ft. (30m)
	0.05luxF1.6(AGC ON), 0Lux with IR ON
	Fixed 0.1"(2.8mm) Lens @F1.6; Horizontal Field of View: 100.4°
Lens Mount	
	Pan: 0°~355°, Tilt: 0°~67°, Rotation: 0°~355°
Wide Dynamic Range	
	Yes (3D DNR)
Backlight Compensation (BLC) Defog	
HLC	
Sharpness	
	Support for 12 Different Languages
VIDEO STREAM	Support of 12 Difference anguages
Max. Image Resolution	2592 × 1520
Primary Stream	
	(2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720): 30fps / HFR Mode: (1920 x 1080, 1280 x 720): 60fps
Secondary Stream	
Tertiary Stream	
Video Compression	
Video Bit Rate	64 Kbps~8Mbps (CBR / VBR Adjustable)
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc.
NETWORK	
	1 x RJ45 10M / 100M Ethernet Port
Network Storage	
Remote Monitoring	
Online Connections	
Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
AUDIO	
Audio Compression	
	1CH Built-in MIC
Audio I/O	1/1
SYSTEM	
Alarm	
Advanced Function	Built-in Micro SD Card Slot; Up to 128 GB Video Masking, Non-Photosensitive Switch, Watermarking, IP Address Filtering, Image Distortion
Advanced Function	Correction, Heartbeat Tracking
Event Trigger	
Event Action	
Video Analytics	Region Entrance, Region Exit, Intrusion Detection, Line Crossing Detection, Human Counting, Vehicle Counting, Human Tracking,
	Face Capture, Face Detection, Heat Map, Crowd Density Detection, Video Tampering Detection, Scene Change Detection,
	Abandoned Object Detection, Missing Object Detection
GENERAL	
Supported Protocols	ONVIF Profiles S, G, and T
	DC 12V (±10%) / PoE(802.3af)
Power Consumption	<7W
Hardware Reset	
Ingress Protection	
Housing Protection	
Working Environment	
Working Humidity	
Weight	
Dimensions	4.69" x 3.44" (119.0mm x 87.4mm)



Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon\_aivo website: avycon.com